NSN 4820-01-286-6623

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-286-6623

Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
90.0 pounds per square inch
Outside Diameter:
6.125 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
4.312 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
4.312 inches
Bolt Circle Diameter:
5.000 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-286-6623

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0