NSN 4820-01-287-4843

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-287-4843

| Pipe Size Accommodated: |
|--|
| 2.000 inches all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Threaded |
| Connection Style: |
| Socket all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Unthreaded internal pipe all ends |
| Maximum Operating Pressure: |
| 700.0 pounds per square inch single response |
| Criticality Code Justification: |
| Zzzy |
| Special Features: |
| Bonnet material-cuni-mil-c-15726 |
| Material: |
| Nickel alloy flow control device |
| Material Specification: |
| Qq-n-281, cl a or b federal specification single material response stem |
| Media For Which Designed: |
| Water-oil-gas single response |
| Furnished Items And Quantity: |
| 1 handwheel |
| Reference Number Differentiating Characteristics: |
| Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A046b0 |
| Mil-std (military Standard): |
| Mil-c-15726 spec. |