

View Online at <https://aerobasegroup.com/nsn/4820-01-288-5255>

**Pipe Size Accommodated:**

2.000 inches all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Threaded

**Maximum Operating Temp:**

406.0 degrees fahrenheit single response

**Connection Style:**

Socket all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Unthreaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

200.0 pounds per square inch 2nd response

**Material:**

Plastic polytetrafluoroethylene flow control device

**Material Specification:**

Astm b-62 assn standard single material response seat

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved source; 12168 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Specification Data:**

59646-mss-sp-80 professional/industrial association standard

**Specification Or Standard:**

1 type and 125 class and b end and 2.000 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0