## NSN 4820-01-288-5775

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-288-5775

Thread Class:

| Thread Class:                                 |
|---|
| 3a 1st end                                    |
| Thread Direction:                             |
| Right-hand all ends                           |
| Flow Control Device:                          |
| Poppet  |
| Maximum Operating Temp:                       |
| 200.0 degrees fahrenheit 2nd response         |
| Connection Style:                             |
| Plain (pipe) 2nd end                          |
| Valve Operation Method:                       |
| Automatic                                     |
| Connection Type:                              |
| Threaded external pipe 2nd end                |
| Mounting Position:                            |
| Horizontal                                    |
| Thready Qty Per Inch (tpi):                   |
| 12 1st end                                    |
| Maximum Operating Pressure:                   |
| 3000.0 pounds per square inch single response |
| Thread Size:                                  |
| 1.062 inches 1st end                          |
| Seat Angle:                                   |
| 37.0 degrees 1st end                          |
| Material:                                     |
| Steel comp 304 flow control device            |
| Media For Which Designed:                     |
| Hydraulic fluid, mineral base 2nd response    |
| Style Designator:                             |
| Straight thru                                 |
| Thread Series Designator:                     |
| Un 1st end                                    |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |
| Ma  |

No

Fiig:

A530b0