

View Online at <https://aerobasegroup.com/nsn/4820-01-289-8272>

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 1st end

Connection Style:

G46b plain (pipe) 2nd end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Threaded external pipe 2nd end

Features Provided:

Bonnet packing

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

1.500 inches 2nd end

Outside Diameter:

5.000 inches 1st end

Thickness:

0.500 inches 1st end

Bolt Hole Diameter:

0.625 inches 1st end

Bolt Circle Diameter:

3.875 inches 1st end

Flange Face Design:

Plain 1st end

Special Features:

Hose cap and chain

Material:

Copper alloy 922 flow control device or copper alloy 836 flow control device

Material Specification:

Stm b147, alloy 8a assn standard single material response stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 30263 has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Npt 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0