

View Online at <https://aerobasegroup.com/nsn/4820-01-289-8272>

**Thread Direction:**

Right-hand 2nd end

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 1st end

**Connection Style:**

G46b plain (pipe) 2nd end

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes 1st end

**Connection Type:**

Threaded external pipe 2nd end

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Thread Size:**

1.500 inches 2nd end

**Outside Diameter:**

5.000 inches 1st end

**Thickness:**

0.500 inches 1st end

**Bolt Hole Diameter:**

0.625 inches 1st end

**Bolt Circle Diameter:**

3.875 inches 1st end

**Flange Face Design:**

Plain 1st end

**Special Features:**

Hose cap and chain

**Material:**

Copper alloy 922 flow control device or copper alloy 836 flow control device

**Material Specification:**

Stm b147, alloy 8a assn standard single material response stem

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 30263 has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Npt 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0