NSN 4820-01-290-9063

Safety Relief Valve - Page 1 of 2





egroup.com/nsn/4820-01-290-9063

View Online at https://aerobasegroup.com
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
300.0 degrees fahrenheit single response
Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Adjustable Pressure Range:

+101.0/+140.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Thickness:

0.625 inches all ends

First Connection Face To Centerline Distance:

5.375 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

5.500 inches

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Plain all ends

Material:

Stainless steel stem

Media For Which Designed:

Air 1st response

NSN 4820-01-290-9063

Safety Relief Valve - Page 2 of 2

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

