## NSN 4820-01-291-1553

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-291-1553

| Flow Control Device:  |
|---|
| Disk  |
| Bonnet Type:  |
| Inside screw  |
| Bonnet Attachment Method:   |
| Bolted  |
| Bolt Hole Quantity:   |
| 10 all ends   |
| Valve Operation Method:   |
| Automatic   |
| Flange Shape:   |
| Round with holes all ends   |
| Connection Type:  |
| Flange all ends   |
| Mounting Facility:  |
| Bracket   |
| Valve Size:   |
| 5.000 inches  |
| Maximum Operating Pressure:   |
| 250.0 pounds per square inch single response  |
| Outside Diameter:   |
| 9.060 inches all ends   |
| Face To Face Distance:  |
| 16.750 inches   |
| Thickness:  |
| 1.060 inches all ends   |
| Bolt Hole Diameter:   |
| 0.690 inches all ends   |
| Bolt Circle Diameter:   |
| 7.810 inches all ends   |
| Flange Face Design:   |
| Plain all ends  |
| Material:   |
| Rubber synthetic flow control device and nickel alloy 400 flow control device or nickel alloy r-405 flow control device |
| Material Specification:   |
| Qq-n-288, comp d federal specification single material response seat  |
| Style Designator:   |
| Err-090   |
| Furnished Items And Quantity:   |
| 1 cover and 1 chain and 1 sight gage and 1 stem test connection and 1 relief plug and 1 cap                             |
| Shelf Life:   |

N/a

## NSN 4820-01-291-1553

Globe Valve - Page 2 of 2



| U | n | it | Of | Μe | eas | ur | e: |
|---|---|----|----|----|-----|----|----|
|   |   |    |    |    |     |    |    |

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-b-16541 spec.