## NSN 4820-01-292-6747

Y Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-292-6747

| Flow Control Device:   |
|--|
| Disk   |
| Bonnet Type:   |
| Outside screw-yoke   |
| Bonnet Attachment Method:  |
| Bolted   |
| Bolt Hole Quantity:  |
| 4 all ends   |
| Valve Operation Method:  |
| Manual   |
| Flange Shape:  |
| Round with holes all ends  |
| Connection Type:   |
| Flange all ends  |
| Valve Size:  |
| 4.000 inches   |
| Maximum Operating Pressure:  |
| 250.0 pounds per square inch single response   |
| Outside Diameter:  |
| 7.688 inches all ends  |
| Face To Face Distance:   |
| 12.500 inches  |
| Thickness:   |
| 1.000 inches all ends  |
| Bolt Hole Diameter:  |
| 0.688 inches all ends  |
| Bolt Circle Diameter:  |
| 5.312 inches all ends  |
| Flange Face Design:  |
| Plain all ends   |
| Material:  |
| Copper alloy 922 bodyplastic polychlorotrifluoroethylene flow control devicenickel alloy seatnickel alloy stem |
| Media For Which Designed:  |
| Water-oil-gas single response  |
| Style Designator:  |
| Err-090  |
| Furnished Items And Quantity:  |
| 1 handwheel  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 4820-01-292-6747

Y Valve - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A046b0