NSN 4820-01-293-3025

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-293-3025

Body Material:
Aluminum alloy, qq-a-225/8, alloy 6061, t6
Body Style:
Straight thru
Media For Which Designed:
Oil
First End Connection Type:
Threaded internal tube
First End Style Designator:
Gasket seal
First End Outside Diameter Tube Accommodated:
0.625 inches
First End Thread Size And Series/type Designator:
7/8-14 unjf
First End Thread Class:
3b
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Not identical
Second End Connection Type:
Threaded internal tube
Second End Style Designator:
Plain
Second End Outside Diameter Tube Accommodated:
0.625 inches
Second End Thread Size And Series/type Designator:
7/8-14 unjf
Second End Thread Class:
3b
Second End Thread Direction:
Right-hand
First End Seat Angle In Deg:
45.0
Flow Control Device:
Disk
End Connection Quantity:
2
Valve Discharge Flow Rate:
7.5 gallons per minute
Shelf Life:

N/a

NSN 4820-01-293-3025

Calibrated Flow Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A21100