NSN 4820-01-293-8529

Safety Relief Valve - Page 1 of 2

Thread Direction:



View Online at https://aerobasegroup.com/nsn/4820-01-293-8529

Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
End Application:
F/a-18 hornet aircraft
Connection Style:
G46b plain (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe all ends
Adjustable Pressure Range:
+5.0/+140.0 pounds per square inch
Thread Size:
0.250 inches all ends
Criticality Code Justification:
Feat
Opening Pressure Setting:
50.0 pounds per square inch
Special Features:
To be cleaned iaw mil-c-81302
Material:
Steel comp 303 body
Material Specification:
Astm a582 assn standard single material response body
Media For Which Designed:
Oxygen, gaseous single response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Err-090

Style Designator:

NSN 4820-01-293-8529

Safety Relief Valve - Page 2 of 2



Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0