NSN 4820-01-294-4817

Gate Valve - Page 1 of 2

150.0 pounds per square inch



View Online at https://aerobasegroup.com/nsn/4820-01-294-4817

riange Diameter:
7.500 inches
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4
Valve Operation Method:
Manual
Connection Type:
Flange, round w/holes
Features Provided:
Bonnet packing
Valve Size:
6.000 inches
Body Material:
Copper alloy 922 or copper alloy 836
Stem Type:
Nonrising
Body Material Specification:
Astm b61 assn standard single material response or astm b62 assn standard single material response
Face To Face Distance:
8.000 inches
Flange Face Design:
Plain
Disk Material:
Copper alloy 922 or copper alloy 836
Seat Material:
Copper alloy 922 or copper alloy 836
Stem Material:
Err-030
Disk Material Specification:
Astm b61 assn standard single material response or astm b62 assn standard single material response
Seat Material Specification:
Astm b61 assn standard single material response or astm b62 assn standard single material response
Err Default:
Err default
Inlet Relationship With Outlet:
Identical
Pressure Class:

NSN 4820-01-294-4817

Gate Valve - Page 2 of 2



B 4		-:-	ı .
IVI	ate	rıa	13.

Copper alloy 922 or copper alloy 836 seat

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500a0