

View Online at <https://aerobasegroup.com/nsn/4820-01-294-4817>

Flange Diameter:

7.500 inches

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4

Valve Operation Method:

Manual

Connection Type:

Flange, round w/holes

Features Provided:

Bonnet packing

Valve Size:

6.000 inches

Body Material:

Copper alloy 922 or copper alloy 836

Stem Type:

Nonrising

Body Material Specification:

Astm b61 assn standard single material response or astm b62 assn standard single material response

Face To Face Distance:

8.000 inches

Flange Face Design:

Plain

Disk Material:

Copper alloy 922 or copper alloy 836

Seat Material:

Copper alloy 922 or copper alloy 836

Stem Material:

Err-030

Disk Material Specification:

Astm b61 assn standard single material response or astm b62 assn standard single material response

Seat Material Specification:

Astm b61 assn standard single material response or astm b62 assn standard single material response

Err Default:

Err default

Inlet Relationship With Outlet:

Identical

Pressure Class:

150.0 pounds per square inch

Material:

Copper alloy 922 or copper alloy 836 seat

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500a0