

View Online at https://aerobasegroup.com/nsn/4820-01-294-6055

В	ody Material:
S	teel, corrosion resisting
В	ody Style:
S	traight thru
S	tem Material:
S	teel, corrosion resisting
N	ledia For Which Designed:
Н	lydrocarbon fuels and oils
F	irst End Connection Type:
U	Inthreaded internal tube
F	irst End Style Designator:
S	ocket
F	irst End Outside Diameter Tube Accommodated:
1	.500 inches
S	econd End Relationship With First End:
lo	dentical
S	eat Material:
Ρ	lastic, polytetrafluoroethylene
Р	acking Material:
Ρ	lastic, polytetrafluoroethylene
F	low Control Device:
Ρ	iston, spring loaded
F	low Control Device Material:
S	teel, corrosion resisting
E	nd Connection Quantity:
2	
R	egulation Type:
A	utomatic single stage
v	alve Loading Method:
S	pring
N	laximum Inlet Pressure Rating:
6	000.0 pounds per square inch
F	ilter:
N	lot included
т	empurature Rating:
1	50.0 degrees fahrenheit
S	helf Life:
N	l/a
U	Init Of Measure:
D	emilitarization:

No

## NSN 4820-01-294-6055

Fluid Pressure Regulating Valve - Page 2 of 2

**Fiig:** A21100

