## NSN 4820-01-294-7214

Safety Relief Valve - Page 1 of 2

Thread Direction:
Right-hand 2nd end
Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-294-7214

Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
3 1st end
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 1st end
Connection Type:
Threaded internal pipe 2nd end
Adjustable Pressure Range:
+16.0/+30.0 pounds per square inch
Thread Size:
0.250 inches 2nd end
Outside Diameter:
3.250 inches 1st end
Thickness:
0.438 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
<b>Bolt Circle Diameter:</b>
2.125 inches 1st end
Flange Face Design:
Plain all ends
Material:
Copper alloy body
Style Designator:
Err-090
Thread Series Designator:
Npt 2nd end
Shelf Life:
N/a
Unit Of Measure:

## NSN 4820-01-294-7214

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0