NSN 4820-01-295-3728

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-295-3728

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 all ends
End Application:
Los angeles class ss (688)
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+51.0/+70.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Outside Diameter:
5.188 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
5.375 inches
Bolt Circle Diameter:
4.438 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Adjusting lever included
Material:
Ctainless steel stem

Stainless steel stem

NSN 4820-01-295-3728

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: No

Fiig:

A046b0