# NSN 4820-01-295-3728

Safety Relief Valve - Page 1 of 2



Flow Control Device:

Disk

Bonnet Type:

Inside spring

**Bonnet Attachment Method:** 

Union

## **Disk Loading Method:**

Spring

## **Bolt Hole Quantity:**

6 all ends

#### End Application:

Los angeles class ss (688)

#### Valve Operation Method:

Automatic

## Flange Shape:

Round with holes all ends

#### **Connection Type:**

Flange all ends

## Valve Size:

2.000 inches

# Adjustable Pressure Range:

+51.0/+70.0 pounds per square inch

## Maximum Operating Pressure:

200.0 pounds per square inch single response

#### **Outside Diameter:**

5.188 inches all ends

#### Thickness:

0.500 inches all ends

# First Connection Face To Centerline Distance:

5.500 inches

#### **Bolt Hole Diameter:**

0.562 inches all ends

#### Second Connection Face To Centerline Distance:

5.375 inches

#### **Bolt Circle Diameter:**

4.438 inches all ends

#### Flange Face Design:

Plain all ends

# **Special Features:**

Adjusting lever included

# Material:

Stainless steel stem



# NSN 4820-01-295-3728

Safety Relief Valve - Page 2 of 2

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A046b0

