NSN 4820-01-296-7928

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-296-7928

Pipe Size Accommodated:
2.000 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Nimitz class cvn
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic or manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+75.0/+89.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Material:
Nickel alloy flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Specification Data:
81349-mil-v-24332 government specification
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-296-7928

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.