NSN 4820-01-298-5242

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-298-5242

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
500.0 degrees fahrenheit single response
End Application:
Virginia class cg (41)
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+106.0/+120.0 pounds per square inch
Maximum Operating Pressure:
275.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.344 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.344 inches
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
4.075 in all and all

1.375 inches all ends

NSN 4820-01-298-5242

Safety Relief Valve - Page 2 of 2



М			

Steel uns j03002 body

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0