

View Online at <https://aerobasegroup.com/nsn/4820-01-299-4008>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

8.000 inches

Outside Diameter:

13.500 inches all ends

Face To Face Distance:

19.500 inches

Thickness:

1.125 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

11.750 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

9.688 inches all ends

Special Features:

Stop check type; one piece bonnet

Material:

Steel uns k03504 flow control device

Material Specification:

Mil-p-17303 military specification single material response packing

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 57574 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-p-17303 spec.