

View Online at <https://aerobasegroup.com/nsn/4820-01-299-5674>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

406.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.000 inches

Maximum Operating Pressure:

225.0 pounds per square inch 2nd response

Outside Diameter:

4.250 inches all ends

Face To Face Distance:

4.188 inches

Thickness:

0.375 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

3.125 inches all ends

Flange Face Design:

Plain all ends

Material:

Plastic polytetrafluoroethylene packing

Material Specification:

Astm b62 assn standard single material response body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 82666 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0