## NSN 4820-01-301-4244

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-301-4244

Flow Control Device:
Disk
Disk Loading Method:
Spring  Polit Hole Cuantitus
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
450.0 degrees fahrenheit 1st response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
4.000 inches
Maximum Operating Pressure:
300.0 pounds per square inch 1st response
Outside Diameter:
9.000 inches all ends
Face To Face Distance:
11.250 inches
Thickness:
0.688 inches all ends
Bolt Hole Diameter:
0.750 inches all ends
Bolt Circle Diameter:
7.500 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Washer used in 4 in. And above; cotter pin used on 2 1/2 in. And above
Material:
Nickel alloy seat
Material Specification:
Qq-s-288 federal specification single material response seat
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Washer used in 4 in. And above; cotter pin used on 2 1/2 in. And above  Material:  Nickel alloy seat  Material Specification:  Qq-s-288 federal specification single material response seat  Media For Which Designed:  Water-oil-gas 2nd response

Straight through flanged ends

## NSN 4820-01-301-4244

Check Valve - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530b0