

View Online at <https://aerobasegroup.com/nsn/4820-01-301-9068>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

406.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

300.0 pounds per square inch 2nd response

Thread Size:

0.500 inches all ends

Material:

Silicon stem and copper alloy stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 14959, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Npt all ends

Furnished Items And Quantity:

1 handwheel

Specification Data:

59646-definite specification mss sp-80 professional/industrial association specification

Specification Or Standard:

li type and 150 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0