

View Online at <https://aerobasegroup.com/nsn/4820-01-301-9885>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

500.0 degrees fahrenheit 2nd response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

2.000 inches

Maximum Operating Pressure:

225.0 pounds per square inch 2nd response

Outside Diameter:

6.000 inches all ends

Face To Face Distance:

7.250 inches

Thickness:

0.625 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Material Specification:

Astm wpc alloy 69 assn standard single material response stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 48422, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0