## NSN 4820-01-304-1436



Vie 0-01-304-1436

| <b>NSN 4820-01-304-1436</b><br>Globe Valve - Page 1 of 1 |
|--|
| View Online at https://aerobasegroup.com/nsn/4820        |
| Pipe Size Accommodated:                                  |
| 0.250 inches all ends                                    |
| Flow Control Device:                                     |
| Disk   |
| Bonnet Type:   |
| Outside screw-yoke                                       |
| Bonnet Attachment Method:                                |
| Bolted   |
| Renewable Seat Ring Type:                                |
| Pressed-in   |
| Maximum Operating Temp:                                  |
| 1000.0 degrees fahrenheit 1st response                   |
| Connection Style:  |
| Socket all ends  |
| Valve Operation Method:                                  |
| Manual   |
| Connection Type:   |
| Unthreaded internal pipe all ends                        |
| Features Provided:                                       |
| Bonnet packing   |
| Maximum Operating Pressure:                              |
| 235.0 pounds per square inch 1st response                |
| Special Features:  |
| Loose disc   |
| Material:  |
| Steel  |
| Media For Which Designed:                                |
| Water-oil-gas 2nd response                               |
| Style Designator:  |
| Err-090  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A046b0   |
|  |
|  |
|  |