NSN 4820-01-305-2017

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-305-2017

Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+331.0/+495.0 pounds per square inch
Maximum Operating Pressure:
285.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
1.750 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.125 inches
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.375 inches all ends
Material:
Steel comp 316 stem

NSN 4820-01-305-2017

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0