NSN 4820-01-305-5758

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-305-5758

Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
95.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
6.000 inches
Adjustable Pressure Range:
+45.0/+50.0 pounds per square inch
Maximum Operating Pressure:
140.0 pounds per square inch single response
Outside Diameter:
13.500 inches 1st end
Thickness:
1.125 inches 1st end
First Connection Face To Centerline Distance:
10.000 inches
Bolt Hole Diameter:
0.875 inches all ends
Second Connection Face To Centerline Distance:
10.922 inches
Bolt Circle Diameter:
9.500 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
8.500 inches 2nd end
Material:
Stainless steel flow control device

NSN 4820-01-305-5758

Safety Relief Valve - Page 2 of 2



Media For Which Designe	ed:
-------------------------	-----

Steam single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0