## NSN 4820-01-306-0997

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-306-0997

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
8 2nd end
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
10.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
185.0 pounds per square inch
Outside Diameter:
16.000 inches 1st end
Thickness:
0.062 inches 2nd end
First Connection Face To Centerline Distance:
11.000 inches
Bolt Hole Diameter:
1.000 inches 1st end
Second Connection Face To Centerline Distance:
10.875 inches
Bolt Circle Diameter:
14.250 inches 1st end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
10.625 inches 2nd end

## NSN 4820-01-306-0997

Safety Relief Valve - Page 2 of 2



wateriai:
Stainless steel flow control device
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0