## NSN 4820-01-306-0998

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bolt Hole Quantity:** 

**Maximum Operating Temp:** 

100.0 degrees fahrenheit single response

Disk

8 all ends



View Online at https://aerobasegroup.com/nsn/4820-01-306-0998

3
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
6.000 inches
Adjustable Pressure Range:
+50.0/+58.0 pounds per square inch
Maximum Operating Pressure:
160.0 pounds per square inch single response
Outside Diameter:
13.500 inches 1st end
Thickness:
1.125 inches 1st end
First Connection Face To Centerline Distance:
9.500 inches
Bolt Hole Diameter:
0.875 inches all ends
Second Connection Face To Centerline Distance:
9.438 inches
Bolt Circle Diameter:
9.500 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
8.500 inches 2nd end
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

## NSN 4820-01-306-0998

Safety Relief Valve - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0