NSN 4820-01-306-1403

Globe Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Outside screw-yoke

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-306-1403

Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
550.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
9.000 inches all ends
Face To Face Distance:
11.500 inches
Thickness:
0.938 inches all ends
Bolt Hole Diameter:
0.750 inches all ends
Bolt Circle Diameter:
7.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
6.188 inches all ends
Material:
Iron alloy body
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-306-1403

Globe Valve - Page 2 of 2



Furnished	Items	And	Quantity:	
ullisiicu	1101113	Allu	wuantit.	

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0