NSN 4820-01-306-3066

Cross Valve - Page 1 of 2

Flow Control Device:

Stem

Bonnet Type: Inside screw



View Online at https://aerobasegroup.com/nsn/4820-01-306-3066

Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
6.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
11.000 inches all ends
Face To Face Distance:
20.000 inches
Thickness:
1.000 inches all ends
First Connection Face To Centerline Distance:
7.870 inches
Bolt Hole Diameter:
0.875 inches 2nd end
Bolt Circle Diameter:
9.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.060 inches all ends
Raised Face Diameter:
8.500 inches all ends
Special Features:
Third end bolt holes threaded 3/4-10unc through tapped holes
Material:
Stainless steel stem
Media For Which Designed:
Oil, lubricating, diester base single response

NSN 4820-01-306-3066

Cross Valve - Page 2 of 2



Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0