NSN 4820-01-306-4551

Safety Relief Valve - Page 1 of 2



Salety Keller valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-01-306-4551
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Opening Pressure Setting:
285.0 pounds per square inch
Outside Diameter:
6.000 inches 1st end
Thickness:
0.625 inches 1st end
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:

4.125 inches

Bolt Circle Diameter:

4.750 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

3.625 inches 1st end

Material:

Stainless steel stem

Media For Which Designed:

Water-oil-gas single response

NSN 4820-01-306-4551

Safety Relief Valve - Page 2 of 2



Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0