NSN 4820-01-306-6211

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-306-6211

Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
567.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Valve Size:
1.500 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
5.000 inches all ends
Face To Face Distance:
6.500 inches
Thickness:
0.562 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.875 inches all ends
Material:
Steel comp 420 flow control device
Media For Which Designed:
Oil 1st response

NSN 4820-01-306-6211

Stop-check Valve - Page 2 of 2



Sty				

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0