NSN 4820-01-307-5731

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-307-5731

Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+12.0/+15.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
3.562 inches all ends
Thickness:
0.312 inches all ends
First Connection Face To Centerline Distance:
3.438 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.438 inches
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Plain all ends
Material:
Steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-307-5731

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0