NSN 4820-01-307-8762

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:

Bonnet Attachment Method:

2.500 inches 2nd end Flow Control Device:

Disk

Bonnet Type: Inside screw

Threaded



View Online at https://aerobasegroup.com/nsn/4820-01-307-8762

Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+908.0/+1011.0 pounds per square inch
Outside Diameter:
7.000 inches 1st end
Thickness:
0.875 inches 2nd end
First Connection Face To Centerline Distance:
6.000 inches
Bolt Hole Diameter:
0.875 inches 2nd end
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
4.125 inches 1st end
Material:
Stainless steel flow control device
Style Designator:
Err-090

NSN 4820-01-307-8762

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0