NSN 4820-01-307-9307

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-307-9307 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Seat Angle: 37.0 degrees all ends **Opening Pressure Setting:** 2.0 pounds per square inch **Special Features:** Other media utilized: alcohol, lube oil, nitrogen, water Material: Rubber butadiene-acrylonitrile class nbr seat **Material Specification:** Qq-a-225/6 federal specification single material response body Media For Which Designed: Hydrogen 4th response **Style Designator:** Straight thru **Thread Series Designator:** Unjf all ends Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4820-01-307-9307

Check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-p-25732 spec.