NSN 4820-01-307-9309

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-307-9309

DISK
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+156.0/+180.0 pounds per square inch
Maximum Operating Pressure:
350.0 pounds per square inch single response
Outside Diameter:
9.000 inches 1st end
Thickness:
1.125 inches 2nd end
First Connection Face To Centerline Distance:
6.094 inches
Bolt Hole Diameter:
0.875 inches 2nd end
Second Connection Face To Centerline Distance:
6.969 inches
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
6.188 inches 1st end
Material:
Steel body

NSN 4820-01-307-9309

Safety Relief Valve - Page 2 of 2



Style Designator:	
Err-090	
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization: No

Fiig:

A046b0