## NSN 4820-01-308-5209

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-308-5209

••
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Maximum Operating Pressure:
225.0 pounds per square inch single response
Opening Pressure Setting:
75.0 pounds per square inch
Outside Diameter:
9.000 inches 2nd end
Thickness:
1.000 inches 1st end
First Connection Face To Centerline Distance:
8.250 inches
Bolt Hole Diameter:
0.875 inches 1st end
Second Connection Face To Centerline Distance:
7.750 inches
Bolt Circle Diameter:
9.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.688 inches 2nd end
Raised Face Diameter:
8.500 inches 1st end
Material:
Steel comp 416 stem

## NSN 4820-01-308-5209

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
G.1.011 Z.1.01

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0