

View Online at <https://aerobasegroup.com/nsn/4820-01-310-7682>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

800.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

2.500 inches

Maximum Operating Pressure:

285.0 pounds per square inch single response

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

8.500 inches

Thickness:

0.880 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

4.120 inches all ends

Material:

Steel uns j03002 body

Material Specification:

Astm a216, wcb assn standard single material response body

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0