NSN 4820-01-311-9464

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-311-9464

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Pressure tight outlet side
Valve Size:
2.000 inches
Adjustable Pressure Range:
+65.0/+74.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
6.000 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
4.000 inches
Bolt Circle Diameter:
4.750 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel stem

NSN 4820-01-311-9464

Safety Relief Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Specification Data:
81349-mil-v-24332 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A046b0

Mil-std (military Standard):

Mil-v-24332 spec.