

View Online at <https://aerobasegroup.com/nsn/4820-01-311-9464>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Pressure tight outlet side

Valve Size:

2.000 inches

Adjustable Pressure Range:

+65.0/+74.0 pounds per square inch

Maximum Operating Pressure:

400.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

4.500 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

4.000 inches

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Plain all ends

Material:

Stainless steel stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Specification Data:

81349-mil-v-24332 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.