## NSN 4820-01-312-0280

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-312-0280

Bonnet Attachment Method:					
Bolted					
Bolt Hole Quantity:					
4 all ends					
Maximum Operating Temp:					
100.0 degrees fahrenheit single response					
Valve Operation Method:					
Automatic					
Flange Shape:					
Round with holes all ends					
Connection Type:					
Flange all ends					
Valve Size:					
1.500 inches					
Adjustable Pressure Range:					
+46.0/+59.0 pounds per square inch					
Maximum Operating Pressure:					
285.0 pounds per square inch single response					
Outside Diameter:					
6.000 inches 1st end					
Thickness:					
0.625 inches 1st end					
First Connection Face To Centerline Distance:					
4.750 inches					
Bolt Hole Diameter:					
0.750 inches 1st end					
Second Connection Face To Centerline Distance:					
4.875 inches					
Bolt Circle Diameter:					
4.750 inches 1st end					
Flange Face Design:					
Raised straight all ends					
Raised Face Height:					
0.062 inches all ends					
Raised Face Diameter:					
3.625 inches 1st end					
Material:					
Stainless steel flow control device					

## NSN 4820-01-312-0280

Safety Relief Valve - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0