

View Online at <https://aerobasegroup.com/nsn/4820-01-313-4535>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

550.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

4.000 inches

Maximum Operating Pressure:

250.0 pounds per square inch 2nd response

Outside Diameter:

9.000 inches all ends

Thickness:

0.938 inches all ends

First Connection Face To Centerline Distance:

5.750 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

5.750 inches

Bolt Circle Diameter:

7.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

6.188 inches all ends

Material:

Plastic polytetrafluoroethylene packing

Material Specification:

Astm b-61 assn standard single material response flow control device

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 12168 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0