NSN 4820-01-313-4547

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-313-4547

Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Adjustable Pressure Range:
+203.0/+226.0 pounds per square inch
Maximum Operating Pressure:
285.0 pounds per square inch single response
Outside Diameter:
9.000 inches 2nd end
Thickness:
1.000 inches 1st end
First Connection Face To Centerline Distance:
9.000 inches
Bolt Hole Diameter:
0.875 inches 1st end
Second Connection Face To Centerline Distance:
7.125 inches
Bolt Circle Diameter:
9.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
8.500 inches 1st end
Material:
Stainless steel flow control device

NSN 4820-01-313-4547

Safety Relief Valve - Page 2 of 2



Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A046b0