NSN 4820-01-313-4549

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-313-4549

| Pipe Size Accommodated: |
|--|
| 1.000 inches 2nd end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 4 1st end |
| Maximum Operating Temp: |
| 425.0 degrees fahrenheit single response |
| Connection Style: |
| Socket with brazing ring err-100 |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Unthreaded internal pipe 2nd end |
| Adjustable Pressure Range: |
| +20.0/+24.0 pounds per square inch |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 4.250 inches 1st end |
| Thickness: |
| 0.375 inches 1st end |
| Bolt Hole Diameter: |
| 0.625 inches 1st end |
| Bolt Circle Diameter: |
| 3.125 inches 1st end |
| Flange Face Design: |
| Plain 1st end |
| Material: |
| Copper alloy body |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |

NSN 4820-01-313-4549

Safety Relief Valve - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A046b0