NSN 4820-01-313-6032

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-01-313-6032

0.750 inches 2nd end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 1st end
Connection Type:
Unthreaded internal pipe 2nd end
Adjustable Pressure Range:
+160.0/+225.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Outside Diameter:
3.812 inches 1st end
Thickness:
0.438 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Bolt Circle Diameter:
2.688 inches 1st end
Flange Face Design:
Plain all ends
Material:
Stainless steel stem
Media For Which Designed:
Gas, inert 2nd response
Style Designator:
Err-090
Shelf Life:
N/a

NSN 4820-01-313-6032

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0