NSN 4820-01-313-8648

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-313-8648

Threaded
Bolt Hole Quantity:
8 1st end
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+491.0/+546.0 pounds per square inch
Maximum Operating Pressure:
3705.0 pounds per square inch single response
Outside Diameter:
7.500 inches 1st end
Thickness:
1.250 inches 2nd end
First Connection Face To Centerline Distance:
6.000 inches
Bolt Hole Diameter:
1.125 inches 2nd end
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
5.875 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
4.125 inches 1st end
Material:
Stainless steel stem

NSN 4820-01-313-8648

Safety Relief Valve - Page 2 of 2



Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0