NSN 4820-01-314-1019

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Disk Loading Method:

Bonnet Type: Inside spring

Disk

Union



View Online at https://aerobasegroup.com/nsn/4820-01-314-1019

Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+1031.0/+1210.0 pounds per square inch
Outside Diameter:
5.875 inches 1st end
Thickness:
1.125 inches 1st end
First Connection Face To Centerline Distance:
3.374 inches
Bolt Hole Diameter:
1.000 inches 1st end
Second Connection Face To Centerline Distance:
3.312 inches
Bolt Circle Diameter:
4.000 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches all ends
Raised Face Diameter:
2.000 inches 1st end
Material:
Stainless steel flow control device
Style Designator:
Err-090

NSN 4820-01-314-1019

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0