NSN 4820-01-314-2513

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-314-2513

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+68.0/+84.0 pounds per square inch
Maximum Operating Pressure:
225.0 pounds per square inch single response
Outside Diameter:
4.250 inches 1st end
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.374 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.312 inches
Bolt Circle Diameter:
3.125 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
2.000 inches 1st end

NSN 4820-01-314-2513

Safety Relief Valve - Page 2 of 2



ΝЛ	2+	er	10	
IVI	aı	œI.	10	I -

Stainless steel stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A046b0