NSN 4820-01-315-0936

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-315-0936

Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.250 inches
Adjustable Pressure Range:
+151.0/+180.0 pounds per square inch
Maximum Operating Pressure:
720.0 pounds per square inch single response
Outside Diameter:
5.250 inches 1st end
Thickness:
0.750 inches 1st end
First Connection Face To Centerline Distance:
3.844 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
3.844 inches
Bolt Circle Diameter:
3.875 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.500 inches all ends
Material:
Steel comp 303 stem

NSN 4820-01-315-0936

Safety Relief Valve - Page 2 of 2



Style Designator:	
Frr-090	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0